



SPECIFICATIONS
 Current Rating: 4A AC,DC
 Voltage Rating: 125V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 10mΩ Max.
 Insulation Resistance: 1000MΩ Min.
 Withstanding Voltage: 1000V AC/minute
 Pin Material: Brass/Tin-plated 100~150u"
 Material: Nylon 66,UL94V-0
 Color: Natural(White)

Ordering Information & Dimensions

| PART NO. | Dimensions | |
|-------------|------------|-------|
| | A | B |
| A2013WV-02P | 2.00 | 5.96 |
| A2013WV-03P | 4.00 | 7.96 |
| A2013WV-04P | 6.00 | 9.96 |
| A2013WV-05P | 8.00 | 11.96 |
| A2013WV-06P | 10.00 | 13.96 |
| A2013WV-07P | 12.00 | 15.96 |
| A2013WV-08P | 14.00 | 17.96 |
| A2013WV-09P | 16.00 | 19.96 |
| A2013WV-10P | 18.00 | 21.96 |
| A2013WV-11P | 20.00 | 23.96 |
| A2013WV-12P | 22.00 | 25.96 |
| A2013WV-13P | 24.00 | 27.96 |
| A2013WV-14P | 26.00 | 29.96 |
| A2013WV-15P | 28.00 | 31.96 |

| | | | | | | |
|------|-------------|------------|---------------------------------|-------|------------------------------------|--|
| | | | | | C N T肯耐特电子有限公司 | |
| | | | UNIT | SCALE | SHEET | TITLE: 2.00mm PITCH 180° WAFER |
| | | | mm | | 1 of 1 | |
| | | | DRAWN BY SUSAN 2001.02.01 | | APPROVED BY HENLY 2001.02.01 | |
| | | | GENERAL TOLERANCE | | | |
| B2 | REVISE | 2007.10.16 | | | | DRAW NO. : A2013WV-XP |
| B1 | REVISE | 2006.05.24 | X.X ±0.25 | | ANGLE ± | |
| B0 | NEW RELEASE | 2006.01.07 | X.XX ±0.15 | | | |
| REV. | DESCRIPTION | DATE | X.XXX ±0.05 | | | |
| | | | | | | REV. B2 |