



■ SPECIFICATIONS

- Voltage Rating: 250VAC/DC
- Current rating: 3A AC/DC
- Withstanding Voltage: 800V AC/minute
- Insulation resistance: 1,000M Ω min
- Temperature range: -25° C - +85° C
- Contact Resistance: 20m Ω max

■ WAFER

- Part No: CNT-2008 (Straight)
- Poles: 3x2-16x2
- Material: Contact: Brass, Tin Plated
Base: Nylon 66 UL 94V-0
- Q`TY: 1,000 pcs/Tape bag

Part NO	Dimensions (mm)	
	A	B
CNT-2008-03x2	4.00	7.90
CNT-2008-04x2	6.00	9.90
CNT-2008-05x2	8.00	11.90
CNT-2008-06x2	10.00	13.90
CNT-2008-07x2	12.00	15.90
CNT-2008-08x2	14.00	17.90
CNT-2008-09x2	16.00	19.90
CNT-2008-10x2	18.00	21.90
CNT-2008-11x2	20.00	23.90
CNT-2008-12x2	22.00	25.90
CNT-2008-13x2	24.00	27.90
CNT-2008-14x2	26.00	29.90
CNT-2008-15x2	28.00	31.90
CNT-2008-16x2	30.00	33.90

2.00mm Wire to Board Connectors Wafer			盐城市肯耐特电子有限公司			TOLERANCE	
			YAN CHENG SHI KEN NAI TE ELECTRONIC CO., LTD.				
			APPROVED BY	SCALE	SCALE	PART NO	
			JIAN FUF HUI	06.06.25			
			CHECKED BY	UNIT			
			HUANG WU	mm			
			DRAWN BY	VER NO	SIZE		
LTR			CHEN CHAO	A	A4	CNT-2008-XXx2	
REVISION RECORD			DATE				