



Part NO	Dimensions (mm)	
	A	B
CNT-2008R-2x2	2.00	6.00
CNT-2008R-3x2	4.00	8.00
CNT-2008R-4x2	6.00	10.00
CNT-2008R-5x2	8.00	12.00
CNT-2008R-6x2	10.00	14.00
CNT-2008R-7x2	12.00	16.00
CNT-2008R-8x2	14.00	18.00
CNT-2008R-9x2	16.00	20.00
CNT-2008R-10x2	18.00	22.00
CNT-2008R-11x2	20.00	24.00
CNT-2008R-12x2	22.00	26.00
CNT-2008R-13x2	24.00	28.00
CNT-2008R-14x2	26.00	30.00
CNT-2008R-15x2	28.00	32.00
CNT-2008R-16x2	30.00	34.00

- SPECIFICATIONS
- Voltage Rating: 250VAC/DC
- Current rating: 3A AC/DC
- Withstanding Voltage: 800V AC/minute
- Insulation resistance: 1,000MΩmin
- Temperature range: -25° C - +85° C
- Contact Resistance: 20mΩ max
- WAFER
- Poles No: CNT-2008R (Straight)
- Poles: 3x2-16x2
- Material: Contact: Brass, Tin Plated
- Q`TY: 1,000 pcs/Tape bag

Base: Nylon 66 UL94V-0

## 2.00mm (.079'') Crimp Style Connectors Wafer

CNT 肯耐特电子有限公司

TOLERANCE  
0 ± 0.25  
.00 ± 0.15  
.000 ± 0.05

APPROVED BY \_\_\_\_\_ SCALE \_\_\_\_\_ SCALE \_\_\_\_\_ PART NO \_\_\_\_\_

CHECKED BY \_\_\_\_\_ UNIT \_\_\_\_\_

DRAWN BY \_\_\_\_\_ mm \_\_\_\_\_ CNT-2008R

VER NO \_\_\_\_\_ SIZE \_\_\_\_\_ -XX

REVISION RECORD DATE

LTR

REVISION RECORD

DATE

3240

A

A4